



NEW

PFT SAMBA S

Airless-spraying technology of entry-class for professional user

Functional description

PFT SAMBA S can be used for almost all materials of interior paints. Its application field includes home painting works up to small professional operations. Thanks to its flexibility and easy handling every construction site can be managed time saving in comparison to the traditional application with paintbrush and roll.

Fields of application

Can be used for all materials, depends on the material producer like:

- ▶ Acrylic paints, water-based
- ▶ Acrylic paints, solvent-activated
- ▶ Interior dispersion paints

Advantages at a glance

- ▶ robust construction of chassis and chrome-plated,
- ▶ stainless and corrosion-protected
- ▶ hose holder integrated
- ▶ easy cleaning and maintenance, without tools
- ▶ brushless geared motor 230 V, 1 phase
- ▶ self-priming pump
- ▶ best price and conditions



All rights and technical changes reserved. We provide guarantee as far as faultless and proper finishing of our machines is concerned. Figures given in relation to output, equipment and performance are based on experience and can vary in case of changing circumstances. Furthermore, the instructions of the material/mortar manufacturers must be observed. Alterations, reprints and photomechanical reproductions, even in extracts, require the permission of Knauf PFT GmbH & Co. KG.

PFT SAMBA S-GB/1M/05.09/ROT



Knauf PFT

Technical Hotline:

▶ +49 9323 31-1818

▶ Phone +49 9323 31-760

▶ Fax +49 9323 31-770

▶ info@pft-iphofen.de

▶ www.pft.eu

Technical data

Part no.	00 12 47 04
Conveying capacity	max. 1.4l/min
Conveying pressure	max. 200 bar
Size of the nozzle	max. 0.019"
Drive	1.05 kW

Dimensions

Total length	approx. 600 mm
Total width	approx. 520 mm
Total height	approx. 720 – 970 mm adjustable in height

Weights

Total weight	approx. 28 kg
---------------------	---------------

PFT SAMBA S

Basic equipment

Spraying gun complete with
 – color pistol
 – high pressure hose 15 m
 – cleaning and service fluid
 – operating instructions

Knauf PFT GmbH & Co. KG
 P.O. Box 60
 97343 Iphofen
 Einersheimer Straße 53
 97346 Iphofen
 Germany

Knauf Gips KG
 Dry construction-, Gypsum plaster-
 and Soil-Systems

Knauf AMF GmbH & Co. KG
 Ceiling Systems

Knauf Integral KG
 Gypsum Fibre Material

Knauf Marmorit GmbH
 Mineral Facade Systems

Knauf Dämmstoffe GmbH
 Polystyrene Insulating
 Material

Knauf Insulation GmbH
 Glasswool-Isolation, XPS

Knauf Perlite GmbH
 aquapanel® CementBoards,
 Perlit